

STRAUB Pipe coupling Series: GRIP Type: 5513V Extraction proof Stainless steel/FPM (FKM)

Tensile pipe coupling for metal pipes. Lighter version for additional weight savings. Depending on the opening, the couplings support a bending angle of 2° to 5°. When installing, the locking screws must be tightened to the correct torque. The required torque is specified on the coupling.

Field of application

- Machinery rooms
- Mechanical and apparatus engineering
- Transport lines

Features

- Tensile pipe coupling
- Suitable for metal pipes

Characteristics

Series: GRIP

Type: 5513V

Shape: Extraction proof

Housing material: Stainless steel

Material quality: 1.4571

Sleeve material: FPM (FKM)

Material bolts: Stainless steel

Material class bolt: 1.4401

Suitable for pipe material: Metal

Suitable for plastic to metal: No

Approvals: Lloyd's Register type approval



External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Pressure rating Industry	Pressure rating Maritime	Length	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Article
mm	mm				mm	°C	°C	
30	30	PN16	PN42	PN16	46.5	-20	180	13454482
33.7	33.7	PN16	PN39	PN16	46.5	-20	180	13454483
42.4	42.4	PN16	PN53	PN16	71	-20	180	13454477
42.4	42.4	PN16	PN33	PN16	46.5	-20	180	13454484
44.5	44.5	PN16	PN30	PN16	46.5	-20	180	13454485
48.3	48.3	PN16	PN28	PN16	46.5	-20	180	13454486
54	54	PN16	PN24	PN16	65	-20	180	13454487
57	57	PN16	PN23	PN16	65	-20	180	13454488
60.3	60.3	PN16	PN23	PN16	65	-20	180	13454489
73	73	PN16	PN21	PN16	65	-20	180	13454490
76.1	76.1	PN16	PN35	PN16	100	-20	180	13454491
84	84	PN16	PN29	PN16	100	-20	180	13454492
88.9	88.9	PN16	PN26	PN16	100	-20	180	13454493
114.3	114.3	PN16	PN22	PN16	100	-20	180	13454478
139.7	139.7	PN16	PN20	PN16	115	-20	180	13454479
168.3	168.3	PN16	PN16	PN16	115	-20	180	13454480

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.