

## ASAHI Y-filter Series: 36 Type: 3756 PVC-U Glued sleeve



### Characteristics

**Series:** 36

**Type:** 3756

**Housing material:** PVC-U

**Connection:** Glued sleeve

**Minimum medium temperature (continuous):** 0 °C

**Maximum medium temperature (continuous):** 60 °C

### Application

- Recommended in: Chemical

| External tube diameter of connection | Pressure rating | Perforation size | With measuring connections | With drain plug | O-ring material | Article  |
|--------------------------------------|-----------------|------------------|----------------------------|-----------------|-----------------|----------|
| mm                                   |                 | mm               |                            |                 |                 |          |
| 20                                   | PN10            | 0.5              | No                         | No              | EPDM            | 13248655 |
| 25                                   | PN10            | 0.5              | No                         | No              | EPDM            | 13248656 |
| 32                                   | PN10            | 0.5              | No                         | No              | EPDM            | 13248657 |
| 40                                   | PN10            | 0.5              | No                         | No              | EPDM            | 13248658 |
| 50                                   | PN10            | 0.5              | No                         | No              | EPDM            | 13248659 |
| 63                                   | PN10            | 0.5              | No                         | No              | EPDM            | 13248660 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.