



## Ball valve PP-R Plastic welded sleeve PN25

### Characteristics

**Construction type:** 2-way  
**Housing construction:** 1-part  
**Housing material:** PP-R  
**Connection:** Plastic welded sleeve  
**Primary spindle seal material:** EPDM

### Characteristics (2)

**Secondary spindle seal material:** EPDM  
**Body seal:** EPDM  
**Minimum medium temperature (continuous):** -15 °C  
**Maximum medium temperature (continuous):** 95 °C

| Nominal inner diameter | External tube diameter of connection<br>mm | Pressure rating | Face to Face norm     | Manual operation | Bore      | Material ball | Seat material | Spindle material | Weight<br>kg | Article  |
|------------------------|--------------------------------------------|-----------------|-----------------------|------------------|-----------|---------------|---------------|------------------|--------------|----------|
| DN15                   | 20                                         | PN25            | Manufacturer standard | Handle           | Full bore | Bronze        | PTFE          | Bronze           | 1.2          | 13250353 |
| DN20                   | 25                                         | PN25            | Manufacturer standard | Handle           | Full bore | Bronze        | PTFE          | Bronze           | 1.3          | 13250356 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.