



STRAUB Pipe coupling Series: Flex2 Type: 5526 Non pull-resistant Stainless steel/EPDM


Non-tensile pipe couplings for all pipe materials. Depending on the opening, the couplings support a bending angle of 2° to 4° and axial movement of 10 mm. When installing, the locking screws must be tightened to the correct torque. The required torque is specified on the coupling.

Field of application

- Water distribution
- Gas pipelines
- Cooling water

Features

- Flexible pipe coupling
- Suitable for both plastic and metal pipes
- Compensation of changes in length



Characteristics

Series: Flex2

Type: 5526

Shape: Non pull-resistant

Housing material: Stainless steel

Material quality: 1.4571

Sleeve material: EPDM

Material bolts: Steel

Suitable for pipe material: Metal/plastic

Suitable for plastic to metal: No

External tube diameter of connection mm	External tube diameter of connection 2 mm	Pressure rating	Pressure rating Maritime	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
219.1	219.1	PN10	PN10	-20	100	13367964
273	273	PN8	PN8	-20	100	13367965
323.9	323.9	PN7	PN7	-20	100	13280923
406.4	406.4	PN5.5	PN5.5	-20	100	13367966

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.