



SMC Filter Regulator + Lubricator series AC20A-B to AC60A-B

- Filter Regulator + Lubricator
- Port sizes 1/8, 1/4, 3/8, 1/2, 3/4 and 1
- Modular, compact and lightweight
- Integrated and other selectable pressure gauges
- Many attachments available
- Made to orders for your special needs: Long bowl, element service indicator, high pressure...

Characteristics

Series: AC-B

Function: Filter-Regulator-Lubricator

Bowl Material: Polycarbonate

Operating temperature: -5 / 60 °C

Size	Port thread type	Port Size In	Filtration level µm	With pressure gauge	Drain type	Flow direction	Self-venting	Adjustment range	Article
20	BSPP (G)	1/4	5	No	Manual	left ? right	Yes	0.05 - 0.85 Mpa	14231145
20	BSPP (G)	1/4	5	Yes	Manual	left ? right	Yes	0.05 - 0.85 Mpa	12230662
30	BSPP (G)	3/8	5	Yes	Manual	left ? right	Yes	0.05 - 0.85 Mpa	12230671
40	BSPP (G)	1/2	5	Yes	Automatic	left ? right	Yes	0.05 - 0.85 Mpa	12230685
40	BSPP (G)	1/2	5	Yes	Manual	left ? right	Yes	0.05 - 0.85 Mpa	12230687

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.