


DIN125A Flat washer Steel zinc plated



Characteristics

- Series: DIN 125A
- Material: Carbon steel
- Surface protection: Galvanic/electrolytic zinc plated
- DIN standard: 125A
- Facet: No
- ISO standard: 7089



| Inner diameter | Outer diameter | Thickness | Suitable for bolt size metric (M..) | Article  |
|----------------|----------------|-----------|-------------------------------------|----------|
| mm             | mm             | mm        |                                     |          |
| 2.2            | 5              | 0.3       | 2                                   | 23689036 |
| 2.7            | 6              | 0.5       | 2.5                                 | 11760638 |
| 2.7            | 6              | 0.5       | 2.5                                 | 11760643 |
| 2.7            | 6              | 0.5       | 2.5                                 | 23689037 |
| 3.2            | 7              | 0.5       | 3                                   | 23689038 |
| 3.2            | 7              | 0.5       | 3                                   | 11760645 |
| 4.3            | 9              | 0.8       | 4                                   | 23689039 |
| 4.3            | 9              | 0.8       | 4                                   | 12692513 |
| 5.3            | 10             | 1         | 5                                   | 11760648 |
| 5.3            | 10             | 1         | 5                                   | 23689040 |
| 6.4            | 12             | 1.6       | 6                                   | 11760649 |
| 6.4            | 12             | 1.6       | 6                                   | 23689041 |
| 6.4            | 12             | 1.6       | 6                                   | 12692514 |
| 7.4            | 14             | 1.6       | 7                                   | 23689042 |
| 8.4            | 16             | 1.6       | 8                                   | 23256093 |
| 8.4            | 16             | 1.6       | 8                                   | 11760651 |
| 8.4            | 16             | 1.6       | 8                                   | 23689043 |
| 8.4            | 16             | 1.6       | 8                                   | 12692506 |
| 10.5           | 20             | 2         | 10                                  | 12692507 |
| 10.5           | 20             | 2         | 10                                  | 11760652 |
| 10.5           | 20             | 2         | 10                                  | 23689044 |
| 10.5           | 20             | 2         | 10                                  | 23256094 |
| 13             | 24             | 2.5       | 12                                  | 23689045 |
| 13             | 24             | 2.5       | 12                                  | 12692508 |
| 15             | 28             | 2.5       | 14                                  | 12692509 |
| 15             | 28             | 2.5       | 14                                  | 23689046 |
| 17             | 30             | 3         | 16                                  | 23689047 |
| 17             | 30             | 3         | 16                                  | 12692510 |
| 19             | 34             | 3         | 18                                  | 12692511 |
| 19             | 34             | 3         | 18                                  | 23689048 |
| 21             | 37             | 3         | 20                                  | 23689049 |
| 21             | 37             | 3         | 20                                  | 11760657 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

| Inner diameter | Outer diameter | Thickness | Suitable for bolt size metric (M...) | Article  |
|----------------|----------------|-----------|--------------------------------------|----------|
| mm             | mm             | mm        |                                      |          |
| 21             | 37             | 3         | 20                                   | 12692512 |
| 46             | 85             | 7         | 45                                   | 23256109 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.