

TESA tesaflex® 4163 Multifunctional soft PVC insulating tape – ideal for electric installations



Characteristics

Series: Tesaflex® 4163

Material: PVC, soft



Application

- As an insulating tape, it's used e.g. to mark cables, but because of its characteristics, it can also be used as a repairing tape. The special adhesive made from acrylate provides a high UV and temperature resistance. The professional insulation tape is therefore highly robust and can be used for up to 104 weeks outdoors. Furthermore, tesaflex® 4163 is also resistant to acids and solvents. tesaflex® 4163 is universal useable and exceptionally qualified for general jobs like: Electric installation work, e.g. insulating cable coating
- Isogeno-gray product variant for color matching in installation work, e.g. for heating pipes
- Splicing applications
- Also suitable for repairs, marking and bundling

Technical Information

- Carrier type: Soft PVC foil Adhesive composition: Acrylate Overall thickness: 0.13 mm Tear-resistance: 30.0 N/cm Adhesive force: 1.8 N/cm Temperature resistant: briefly up to 130 °C

Construction

- tesaflex® 4163 permits is a special formulated Soft PVC tape with a good film flexibility. Due to the UV stable acrylic adhesive it is perfect suitable for permanent applications.

Colour	Width mm	Length m	Thickness mm	Article
Black	12	33	0.15	23330931
Black	15	33	0.15	23330959
Black	19	33	0.15	23330928
Black	25	33	0.15	23330935
Black	30	33	0.15	23330937
Black	38	33	0.15	23330941
Black	50	33	0.15	23330936
Black	100	33	0.15	23330944
Blue	15	33		23330966
Blue	19	33	0.15	23330930
Blue	50	33	0.15	23330939
Green	15	33		23330950
Green	19	33	0.15	23330951
Grey	15	33		23330953
Grey	19	33	0.15	23330954
Grey	25	33	0.15	23330955

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Colour	Width mm	Length m	Thickness mm	Article
Grey	30	33		23330967
Grey	50	33	0.15	23330958
Red	15	33		23330947
Red	19	33	0.15	23330933
Red	30	33	0.15	23330948
Red	50	33	0.15	23330942
White	12	33		23330960
White	15	33	0.15	23330961
White	19	33	0.15	23330929
White	25	33	0.15	23330962
White	30	33	0.15	23330963
Yellow	19	33	0.15	23330932
Yellow	50	33	0.15	23330940

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.