

## 3M Aluminium adhesive tape 425

## **Details**

- Resistant to chemicals to protect surfaces during de-paint process and other chemical masking operations
- Heat and light reflective tape protects surfaces and enhances lighting efficiency
- Improves heating and cooling efficiency to protect temperature sensitive materials
- Thermally conductive tape reflects and dissipates radiant heat
- Due to its low moisture vapour transmission rate, this tape offers excellent sealing and patching performance
- Withstands exposure to flame, weathering, moisture and UV for a strong, long-lasting and reliable bond
- Clean removal after harsh masking applications
- Conforms to curved and uneven surfaces
- $\bullet$  Wide temperature use range from -53 °C to 148 °C

## **Characteristics**

Series: 425 **Type:** 425

Material: Aluminiumfoil

Colour	Width	Length	Thickness	Article
	mm	m	mm	
Aluminium	100	55		23579937
Silver	19	55		23579940
Silver	38	55	0.12	23579942
Silver	50	55		11752471
Silver	50	55		23579943
Silver	75	55	0.12	23579944

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR\_EC000128\_0275\_JLR\_EN\_18.05.2024