



PFERD Buffing wheel, TR, fabric, soft

Pre-polishing of steel and INOX: cloth rings ST or TH with polishing paste PP 1 VP Fe Pre-polishing of aluminium and brass: cloth rings ST or TH

with polishing paste PP 2 VP MS Pre-polishing of non-ferrous metals: cloth rings ST or TH with polishing paste PP 3 VP NE High-gloss polishing

of all metals: cloth rings TW or FL with polishing paste PP 4 HGP High-gloss polishing of plastics: cloth rings TW or FL with polishing paste PP 5 HGP K

Recommended cutting speeds: Cloth rings of type TW and FL achieve their best performance at a recommended cutting speed of 5–15 m/s Cloth rings

of type ST and TH achieve their best performance at a recommended cutting speed of 10–15 m/s

- Cloth rings are used with polishing pastes for pre-polishing and high-gloss polishing.

For very smooth finishes it may be recommended to use several, or even all, types in succession.

Cloth rings are available in four types: ST (sisal fabric) = Coarse pre-polishing TH (hard cloth) = Pre-polishing

TW (soft cloth) = High-gloss polishing

FL (flannel) = High-gloss polishing/buffing

Diameter disc mm	Thickness mm	Article
80	10	23429326
	10	23429327
	10	23429329

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.