



STAUFF Flat steel U-bolt type FB

Characteristics

Type: FA

Size table:

Nominal pipe size	
	DN40
	DN50
	DN65
	DN80
	DN100
	DN125
	DN150
	DN200
	DN250
	DN300
	DN400

Nominal pipe size	Material	Surface protection	Thread size metric [M..]	Outer pipe diameter mm	With saddle piece	Article
DN40	Steel	Untreated	10	48.3	0	11356361
DN50	Steel	Zinc Plated	10	60.3	0	11356681
DN50	Steel	Untreated	10	57	0	11356362
DN50	Steel	Untreated	10	60.3	0	11356363
DN65	Steel	Untreated	10	76.1	0	11356364
DN80	Steel	Untreated	12	88.9	0	11356365
DN100	Steel	Untreated	12	108	0	11356366
DN100	Steel	Untreated	12	114.3	0	11356367
DN125	Steel	Untreated	12	133	0	11356368
DN125	Steel	Untreated	12	139.7	0	11356369
DN150	Steel	Zinc Plated	16	152	0	11356706
DN150	Steel	Untreated	16	159	0	11356370
DN150	Steel	Untreated	16	164	0	11356675
DN150	Steel	Untreated	16	168.3	0	11356371
DN200	Steel	Untreated	16	216	0	11356374
DN200	Steel	Untreated	16	219.1	0	11356375
DN250	Steel	Untreated	20	273	0	11356378
DN300	Steel	Untreated	20	323.9	0	11356380
DN400	Steel	Untreated	24	406.4	0	11356383

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.