


DIN964 Slotted raised countersunk head metal screw Stainless steel A2



Characteristics

Series: DIN 964

Head form: Countersunk head (oval)

Screwing system: Slotted

Material quality: Stainless steel A2

Surface protection: Untreated

DIN standard: 964

ISO standard: 2,010

Type: Stud bolt

Material	Kind of thread	Thread size metric [M..]	Pitch thread	Length mm	Article
Stainless steel	Metric	2.5	0.45	30	11746240
Stainless steel	Metric	3	0.5	10	23728840
Stainless steel	Metric	4	0.7	8	23728866
Stainless steel	Metric	4	0.7	10	23728853
Stainless steel	Metric	4	0.7	16	23728856
Stainless steel	Metric	4	0.7	20	23728857
Stainless steel	Metric	4	0.7	30	23728859
Stainless steel	Metric	5	0.8	6	23728877
Stainless steel	Metric	5	0.8	8	23728880
Stainless steel	Metric	5	0.8	10	23728867
Stainless steel	Metric	5	0.8	12	23728868
Stainless steel	Metric	5	0.8	16	23728869
Stainless steel	Metric	5	0.8	25	23728871
Stainless steel	Metric	5	0.8	30	23728872
Stainless steel	Metric	5	0.8	40	23728874
Stainless steel	Metric	5	0.8	50	23728876
Stainless steel	Metric	6	1	10	23728883
Stainless steel	Metric	6	1	12	23728885
Stainless steel	Metric	6	1	16	23728886
Stainless steel	Metric	6	1	20	23728887
Stainless steel	Metric	6	1	25	23728888
Stainless steel	Metric	6	1	30	23728889
Stainless steel	Metric	6	1	35	23728890
Stainless steel	Metric	6	1	40	23728891
Stainless steel	Metric	6	1	70	23728895
Stainless steel	Metric	6	1	80	23728897

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.