

DIN966Z Raised countersunk head screw with Pozidriv cross recess Stainless steel A4



Characteristics

- Series: DIN 966Z
- Head form: Countersunk head (oval)
- Screwing system: Pozidriv
- Material quality: Stainless steel A4
- Surface protection: Untreated
- DIN standard: 966
- ISO standard: 7,047
- Type: Stud bolt

Material	Kind of thread	Thread size metric [M..]	Pitch thread	Length mm	Article
Stainless steel	Metric	4	0.7	14	11746669
Stainless steel	Metric	4	0.7	35	11746671
Stainless steel	Metric	2.5	0.45	8	24039977
Stainless steel	Metric	3	0.5	6	23729338
Stainless steel	Metric	3	0.5	8	23729339
Stainless steel	Metric	3	0.5	16	23729336
Stainless steel	Metric	4	0.7	10	23729340
Stainless steel	Metric	4	0.7	16	23729342
Stainless steel	Metric	5	0.8	16	23729349
Stainless steel	Metric	6	1	20	23729359

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.