

DIN7500M Thread forming screw countersunk head with Pozidriv cross recess Steel zinc plated



DIN 7500 thread forming screws form their own "female thread" in ready-made holes by thread-rolling into malleable material.

The resulting thread corresponds to standard metric thread.

Advantages:

- thread-cutting becomes unnecessary
- no play in the mating threads
- high vibration resistance
- no chips

Characteristics

Series: DIN 7500D

Surface protection: Galvanic/electrolytic zinc plated

Head form: Countersunk head

Screwing system: Pozidriv

DIN standard: 7500

Hardened: Yes

Thread moulding: Yes

Material	Thread size metric (M..)	Length mm	Article
Steel	2.5	12	11789362
Steel	3	8	23692975
Steel	3	10	11789368
Steel	3	12	11789369
Steel	4	10	23692976
Steel	4	16	23692977
Steel	5	16	11789390
Steel	5	25	11789392
Steel	5	30	11789393
Steel	6	16	11789399
Steel	6	50	11789406

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.