



WEG 3 Phase motor W22Xdb Cast Iron B5T (4p)

Flameproof motors designed to meet the latest market requirements and certifications for Hazardous Areas. Offer high efficiency, low noise and vibration levels and allow applications in severe duties.

Characteristics

Series: W22Xdb

Type: B5T

Speed: 1500 rpm

Mounting: B5T

Number of poles: 4

Full load speed: 1480 rpm

Full load torque: 9.947 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	ATEX Zone	Nominal rated voltage V	Frame size acc. to IEC	Article
IE2	0.25	Zone 1	230/400	71	12962390
IE2	0.37	Zone 1	230/400	71	12962395
IE2	0.55	Zone 1	230/400	80	12962400
IE3	0.25	Zone 1	230/400	71	13192301
IE3	0.37	Zone 1	230/400	71	13192306
IE3	0.55	Zone 1	230/400	80	13192312
IE3	0.75	Zone 1	230/400	80	13192317
IE3	1.1	Zone 1	230/400	90S/L	13192322
IE3	1.5	Zone 1	230/400	90S/L	12962890
IE3	2.2	Zone 1	230/400	100L	13192327
IE3	3	Zone 1	230/400	100L	13192332
IE3	4	Zone 1	400/690	112M	13192337
IE3	5.5	Zone 1	400/690	132S/M	13192342
IE3	7.5	Zone 1	400/690	132S/M	13192357
IE3	9.2	Zone 1	400/690	160M/L	13192360
IE3	11	Zone 1	400/690	160M/L	13192363
IE3	15	Zone 1	400/690	160M/L	13192366
IE3	18.5	Zone 1	400/690	180M/L	13192369
IE3	22	Zone 1	400/690	180M/L	13192372
IE3	30	Zone 1	400/690	200M/L	13192375
IE3	37	Zone 1	400/690	225S/M	13192378
IE3	45	Zone 1	400/690	225S/M	13192381

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.