



WEG 3 Phase motor W22Xdb Cast Iron B5T (6p)

Flameproof motors designed to meet the latest market requirements and certifications for Hazardous Areas. Offer high efficiency, low noise and vibration levels and allow applications in severe duties.

Characteristics

Series: W22Xdb

Type: B5T

Speed: 1500 rpm

Mounting: B5T

Number of poles: 6

Full load speed: 985 rpm

Full load torque: 7.701 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	ATEX Zone	Nominal rated voltage V	Frame size acc. to IEC	Article
IE2	0.18	Zone 1	230/400	71	13022802
IE2	0.25	Zone 1	230/400	71	13022827
IE2	0.37	Zone 1	230/400	80	13022832
IE2	0.55	Zone 1	230/400	80	13022837
IE3	0.18	Zone 1	230/400	71	13192386
IE3	0.25	Zone 1	230/400	80	13192391
IE3	0.37	Zone 1	230/400	80	13192397
IE3	0.55	Zone 1	230/400	80	13192402
IE3	0.75	Zone 1	230/400	90S/L	13192407
IE3	1.1	Zone 1	230/400	100L	13192413
IE3	1.5	Zone 1	230/400	100L	13192418
IE3	2.2	Zone 1	400/690	112M	13192423
IE3	3	Zone 1	400/690	132S/M	13192429
IE3	4	Zone 1	400/690	132S/M	13192434
IE3	5.5	Zone 1	400/690	132S/M	13192439
IE3	7.5	Zone 1	400/690	160M/L	13192442
IE3	9.2	Zone 1	400/690	160M/L	13192445
IE3	11	Zone 1	400/690	160M/L	13192448
IE3	15	Zone 1	400/690	180M/L	13192451
IE3	18.5	Zone 1	400/690	200M/L	13192454
IE3	22	Zone 1	400/690	200M/L	13192457
IE3	30	Zone 1	400/690	225S/M	13192460
IE3	37	Zone 1	400/690	250S/M	13192463

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.