

ANSELL Glove HyFlex® 11-518



Description

An 18-gauge with EN388 Level 3 cut protection. Dyneema Diamond Technology fibre and a thin PU coating bring a new degree of dexterity and tactility for applications with cut risks. The soft ultralight-duty seamless liner breathes to keep hands cool and dry. Enhanced flexibility and fingertip sensitivity with superior comfort.



Ideal Applications

- Final assembly
- Handling & assembly of small or ultra-fine sharp parts
- Injection molding parts assembly
- Machining -special metal blends
- Packaging areas with risk of cut
- Stamping - light & dry
- Wire assembly & fastening

Mechanical risks : EN388:2003 3331; EN388:2016 3X31B

Characteristics

Series: HyFlex®

Type: 11-518

Type: Cut protection

Antistatic: Yes

Silicone-free: No

Length: 210 mm

Gauge: 18

Colour: Blue

Norm: CE Cat. II, EN 338, EN 420, EN ISO 21420, REACH

Approvals: EN 388:2016

Coating Colour: Blue

Coating material: PU Palm

Liner Material: Dyneema® Diamond

Liner Colour: White

Cuff Style: Knitwrist

Characteristics (2)

Material: Nylon, Spandex, Dyneema Diamond Technology

Possible Sensitizer Ingredients: Natural rubber proteins (in knitwrist elastic)

Category II: Yes

EN 388:2016: 3X31B

EN 420:2003 + A1:2009: Yes

Description	Article
Gloves 11-518 HyFlex Size 11	12388317
Gloves 11-518 HyFlex Size 6	12388302
Gloves 11-518 HyFlex Size 7	12388313
Gloves 11-518 HyFlex Size 8	12388314
Gloves 11-518 HyFlex Size 9	12388315
Gloves 11-518 HyFlex Size 10	12388316

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.