

EMMA Safety boot Constans protection level S3 Duo



There's nothing standard about the levels of safety.

The higher, boot like version of the Comodius. The Constans is created from a high quality full grain leather upper and nappa leather lining. It's also been exclusively developed for semiorthopedic adjustments especially where customised in-soles are required. Even when customised and adjusted, the shoe still exceeds European Standards of safety.

Characteristics

Series: Constans

Norm: EN ISO 20345:2011 [E] S3

Safety class: S3

Mid-sole protection: Yes



Protection class occupational shoes	OB	O1	O2	O3	O4	O5
Protective toecap						
Energy absorption in heel		*	*	*	*	*
Fully enclosed heel		*	*	*	*	*
Antistatic properties		*	*	*		
Puncture resistant outsole				*		
Water penetration and absorption protection			*	*	*	*
Water resistant						

Protection class safety shoes	SB	S1	S1P	S2	S3	S4	S5
Protective toecap	*	*	*	*	*	*	*
Energy absorption in heel		*	*	*	*	*	*
Fully enclosed heel		*	*	*	*	*	*
Antistatic properties		*	*	*	*	*	*
Puncture resistant outsole			*		*		*
Water penetration and absorption protection				*	*	*	*
Water resistant						*	*

Shoe size	Shoe size [UK]	Model	Material toecap	Heat resistant outsole	Antistatic	Slip resistance	Article
39	6	Boot	Aluminium	300°C	Yes	SRC	23487487

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Shoe size	Shoe size (UK)	Model	Material toecap	Heat resistant outsole	Antistatic	Slip resistance	Article
40	6.5	Boot	Aluminium	300°C	Yes	SRC	23487488
41	7	Boot	Aluminium	300°C	Yes	SRC	23487489
42	8	Boot	Aluminium	300°C	Yes	SRC	23487490
43	9	Boot	Aluminium	300°C	Yes	SRC	23487491
44	10	Boot	Aluminium	300°C	Yes	SRC	23487492
45	10.5	Boot	Aluminium	300°C	Yes	SRC	23487493
46	11	Boot	Aluminium	300°C	Yes	SRC	23487494
47	12	Boot	Aluminium	300°C	Yes	SRC	23487495

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.