

## GEDORE Torque wrench TORCOFIX K type 4549-4550-4551



Design: Slim design. Double scale for reading [N·m] as well as [lbf·ft] below a window, with magnifying effect. Robust, satin matte chrome-plated tubular steel design with chrome plated ratchet, including ergonomic fibreglass reinforced plastic handle with notches as handling or calibration tool. Due to the integrated ratchet function, controlled directional tightening is guaranteed. Bending mechanism with castor guarantees tactile and acoustic trigger signals. Light and comfortable scale setting by turning the handle and locking on push knob, extremely high accuracy due to micrometer scale ring.

Scale range:

100-550 N·m

75.0 - 405.0 lbf·ft

Delivery includes test certificate DIN EN ISO 6789 and two-language operator manual, in carton.

Application: For controlled screw tightening in the most common torque range from 1-850 N·m, for all industrial manufacturing areas.

| Connection size | Tightening moment<br>Nm | Total length<br>mm | Article  |
|-----------------|-------------------------|--------------------|----------|
| 1/2             | 20 / 100                | 395                | 23071478 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.