


BECK Hand reamer, rapid adjustment, HSS type 1505

Fabrieks-
norm



Design: Right cutting, with replaceable blades made of HSS, factory standard and cylinder shank with square drive. The uneven blade pitch ensure chatter-free and accurate drilling. The reamer can be progressively set within the stated adjustment range. The setting should be made using a ring gauge [order no. 4411]. Bright surface

Application: Particularly suitable for repair work. Only for reaming through-holes. Not suitable for machining blind holes due to the head screw. Particularly suitable for steel materials up to 500 N/mm² in strength e.g. general construction steels, steel materials up to 900 N/mm² in strength such as machine steels, tempered steels, tool steels, case-hardening steels, casting materials and non-ferrous metals such as aluminium, brass, copper and bronzes.



Type	Diameter mm	Cutting length mm	Total length mm	Holding system	Material	Article
Adjustable reamer	8	34	115	Square	HSS	12594371
Adjustable reamer	9	34	115	Square	HSS	12594372
Adjustable reamer	10	34	115	Square	HSS	12594373
Adjustable reamer	11	35	125	Square	HSS	12594374
Adjustable reamer	12	41	135	Square	HSS	12594375
Adjustable reamer	13.5	50	146	Square	HSS	12594376
Adjustable reamer	15.5	60	166	Square	HSS	12594377
Adjustable reamer	18	65	178	Square	HSS	12594378
Adjustable reamer	21	76	195	Square	HSS	12594379
Adjustable reamer	24	82	218	Square	HSS	12594380
Adjustable reamer	27.5	86	245	Square	HSS	12594381
Adjustable reamer	31.5	98	280	Square	HSS	12594382

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.