

3M Hand pad WR-SH



Design: Resin-bonded aluminium oxide abrasive grain (from Order No. 0020 silicon carbide) on fabric fleece, flexible adjustment to the shape of the workpiece.

Application: For cleaning, deburring, finishing and grinding surfaces in the metal, wood and synthetics fields as well as other sectors in industry and trade. Can be used wet and dry. Can be used with hand blocks (Order No. 8451 1000).

Design: Resin-bonded aluminium oxide abrasive grain (from Order No. 0020 silicon carbide) on fabric fleece, evenly scattered, flexible adjustment to the shape of the workpiece. Measurements (L x W) 224 x 158 mm.

Application: For cleaning, deburring, finishing and grinding surfaces in the metal, wood and synthetics sectors, and other markets in industry and trade. Can be used wet and dry. Can be used with hand blocks (Order No. 8451 1000).

Characteristics

Series: WR-SH

Description	Article
Hand pad set fl. WR-SH 158x224mm superfine	23579374

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.