



3M Scotch-Brite Clean & Finish Brush with pin FF-ZS

Design: Aluminium oxide layers [A], very fine with silicon-carbide layers [SiC], strong-bonded to Nylon-fibre fleece, with 6-mm cast shank.

Application: For adjusting previously processed points, such as welds, oxide removal and tarnish as well as for light deburring, cleaning and finishing work. Applicable for straight grinders, boring machines and flexible axles.

Description	Article
Flap brushes FF-ZS shank-Ø 6mm 75x45mm coarse A	12064116
Flap brushes FF-ZS shank-Ø 6mm 75x45mm coarse A	23579333
Flap brushes FF-ZS shank-Ø 6mm 75x45mm fine S	23579335
Scotch-Brite™ Shaft Mounted Flap Brush	23579336
Scotch-Brite™ Shaft Mounted Flap Brush PF-ZS, 100 mm x 45 mm x 6 mm, A CRS	23153261
Scotch-Brite™ Shaft Mounted Flap Brush PF-ZS, 100 mm x 45 mm x 6 mm, A VFN	23579338
3m ff-zs brsh avfn d75x45	23579337

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.