



# FORMAT HSS metric die tolerance 6E type 1801



Design: HSS, EN 22568, closed, pre-slotted form, with spiral point form on both sides from M3. Bright surface

Application: For regular metric threads according to ISO DIN 13.

Note: HSS-E PM is distinguished by its high resilience (stronger edge stability, wear resistance) and a higher tool life.

| Kind of thread | Thread size metric [M..] | Pitch outer thread<br>mm | Material | Article  |
|----------------|--------------------------|--------------------------|----------|----------|
| Metric         | 3                        | 0.5                      | HSS      | 23412647 |
| Metric         | 4                        | 0.7                      | HSS      | 23412648 |
| Metric         | 5                        | 0.8                      | HSS      | 23412649 |
| Metric         | 6                        | 1                        | HSS      | 23412650 |
| Metric         | 8                        | 1.25                     | HSS      | 23412651 |
| Metric         | 10                       | 1.5                      | HSS      | 23412652 |
| Metric         | 12                       | 1.75                     | HSS      | 23412653 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.