

## **BESSEY OMEGA solid steel gluing clamp type 5102**

Design: Slide rail and fixed bracket manufactured from one piece of structurally optimised, cold-drawn profile steel. The patented OMEGA bracket provides the maximum elasticity and security. Even with heavy vibrations, the clamping force is sustained for longer. Mobile bracket made of forged and galvanised zinc-plated heattreatable steel. The smooth-running spindle with rolled, cold-twisted and burnished trapezoidal thread. The mobile pressure plate [Order No. 5104] can be replaced in line with the respective application without tools. With ergonomic 2-component plastic handle.

Application: Flexible clamping for the sensitive and very precise holding of items. The OMEGA bracket ensures a very precise clamping pressure. For high clamping forces with low tool weight. Clamping force up to 5 kN.

Chucking range	Jaw length	Article
mm	mm	
80	80	23288082
100	100	23288083
250	120	23288084
300	140	23288085
400	120	23288086
600	120	23288088

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR\_EC002200\_0040\_MVB\_EN\_18.05.2024