



REMA Spring balancer, heavy-duty version with fixed suspension

Heavy design with solid suspension

- Reduces the workload
- Balancers lock electric and pneumatic tools at the desired working height
- Total weight is carried by the cable
- Construction according to DIN 15112

-

Application

grinding, riveting hammers, drills, etc.

-

Design

Fixing the desired cable length in several places by slight movement of the load

-

Areas of application

for pneumatic and electric tools (drills, screwdrivers, measuring instruments, etc.).

-

Robust material

flexible stainless steel cable.

Aluminium enclosure.

Specifically designed spiral spring for low-noise operation.

-

Variable and safe attachment

adjustable load bearing capacity (button) and cable length.

Rotating lower hook.

Additional safety suspension eye.

Wear resistant cable guide.

Isolated suspension.

Fixing at one point possible.

Description	Article
Spring balancer type 9346 load capacity 2-4kg rope length 2.5m	23794679
Spring balancer type 9347, load capacity 4-6kg, rope length 2.5m	23794680
Spring balancer type 9348 load capacity 6-8kg rope length 2.5m	23794681
Spring balancer type 9349 load capacity 8-10kg rope length 2.5m	24046634
Spring balancer type 9350 load capacity 10-14kg rope length 2.5m	24046635

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.