




FORMAT Circular saw blade hard metal tooth form trapezium surface negative 4 ° type 2683

HM

Design: The cutting speed should not be below 50 m/s for aluminium and not below 30 to 40 m/s for solid material.

Application: Mainly for use on mitre saws with oscillating saw blades or other circular saw benches which cut against the direction of feed. For thin-walled profiles made of aluminium and plastic, particularly anodised profiles.



Blade diameter mm	Material	Thickness mm	Hole diameter mm	Number of teeth	Article
250	Hard metal	3.2	30	60	23113999
250	Hard metal	3.2	30	80	23114000
250	Hard metal	3.2	32	60	23114001
250	Hard metal	3.2	32	80	23114002
275	Hard metal	3.2	40	72	23114003
300	Hard metal	3.2	30	72	23114004
300	Hard metal	3.2	30	96	23114005
300	Hard metal	3.2	32	96	23114006
300	Hard metal	3.2	40	96	23114007
330	Hard metal	3.2	32	100	23114008
350	Hard metal	3.4	30	84	23114009
350	Hard metal	3.4	32	84	23114010
350	Hard metal	3.4	32	108	23114011
350	Hard metal	3.4	40	84	23114012
350	Hard metal	3.4	40	108	23114013
350	Hard metal	3.4	50	84	23114014
400	Hard metal	3.4	40	96	23114016
500	Hard metal	4	30	120	23114018

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.