



FORMAT Circular saw blade hard metal tooth form trapezium surface positive 5 ° type 2680

HM

Design: The cutting speed should not be below 50 m/s for aluminium and not below 30 to 40 m/s for solid material.

Application: Mainly for use on circular saw benches which cut against the direction of feed. For profiles and solid material, format, mitre and longitudinal cuts in aluminium and other non-ferrous metals as well as for cutting synthetic resins, mainly thicker cross-sections.

Blade diameter mm	Material	Thickness mm	Hole diameter mm	Number of teeth	Article
250	Hard metal	3.4	30	60	23113984
250	Hard metal	3.4	30	80	23113985
250	Hard metal	3.4	32	60	23113986
250	Hard metal	3.4	32	80	23113987
275	Hard metal	3.4	40	72	23113988
300	Hard metal	3.4	30	72	23113989
300	Hard metal	3.4	40	96	23113990
350	Hard metal	3.6	30	84	23113991
350	Hard metal	3.6	32	84	23113992
350	Hard metal	3.6	32	108	23113993
350	Hard metal	3.6	40	84	23113994
350	Hard metal	3.6	40	108	23113995
400	Hard metal	3.6	40	96	23113996
420	Hard metal	4	40	96	23113997
500	Hard metal	4	30	120	23113998

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.