

**ERIKS NV** 

## DIN6798J Flat serrated lock washer with internal teeth Spring steel zinc plated

## **Characteristics**

Series: DIN 6798J

Surface protection: Galvanic/electrolytic zinc plated

DIN standard: 6798J

Material	Surface protection	Inner diameter	Outer diameter	Suitable for bolt size metric (M)	Model	Article
		mm	mm			
Carbon steel	Galvanic/electrolytic zinc plated	4.3	8	4	Closed external toothing	11787443
Carbon steel	Galvanic/electrolytic zinc plated	5.3	10	5	Closed external toothing	23688523
Carbon steel	Galvanic/electrolytic zinc plated	6.4	11	6	Closed external toothing	23692080
Carbon steel	Galvanic/electrolytic zinc plated	8.4	15	8	Closed external toothing	11787444
Carbon steel	Galvanic/electrolytic zinc plated	13	20.5	12	Closed external toothing	11787446
Carbon steel	Galvanic/electrolytic zinc plated	17	26	16	Closed external toothing	11787447
Carbon steel	Galvanic/electrolytic zinc plated	25	38	24	Closed external toothing	11787450

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**ERIKS** 

Page 1/1

PR\_EC002345\_0042\_CSC\_EN\_17.05.2024