



# DIN6797J Flat serrated lock washer with open internal teeth

## Spring steel zinc plated

### Characteristics

**Series:** DIN 6797J

**Surface protection:** Galvanic/electrolytic zinc plated

**DIN standard:** 6797J

| Material     | Surface protection                | Inner diameter | Outer diameter | Suitable for bolt size metric (M..) | Model                 | Article  |
|--------------|-----------------------------------|----------------|----------------|-------------------------------------|-----------------------|----------|
|              |                                   | mm             | mm             |                                     |                       |          |
| Carbon steel | Galvanic/electrolytic zinc plated | 3.2            | 6              | 3                                   | Open internal tothing | 23692064 |
| Carbon steel | Galvanic/electrolytic zinc plated | 8.4            | 15             | 8                                   | Open internal tothing | 11787284 |
| Carbon steel | Galvanic/electrolytic zinc plated | 13             | 20.5           | 12                                  | Open internal tothing | 11787286 |
| Carbon steel | Galvanic/electrolytic zinc plated | 17             | 26             | 16                                  | Open internal tothing | 11787287 |
| Carbon steel | Galvanic/electrolytic zinc plated | 25             | 38             | 24                                  | Open internal tothing | 11787290 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.