



ARI Globe valve Series: 45.005 Type: 1417 Steel Butt weld PN40

Characteristics

Series: 45.005
Type: 1417
Norm: EN (DIN)
Construction type: Straight
Housing material: Steel
Surface protection: Standard manufacturers coating
Connection: Butt weld
Standard welding connection: EN 12627
Stem seal type: Gland seal
Material disc: 1.4021+QT
Spindle material: 1.4021+QT
Primary spindle seal material: Graphite
Material bonnet: 1.0619+N

Characteristics (2)

Bonnet gasket material: Stainless steel/graphite
Actuator material: Cast iron
Minimum medium temperature (continuous): -10 °C
Maximum medium temperature (continuous): 450 °C
Maximum pressure difference at 20 °C: 40 bar

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of disc	Type of bonnet	Sealing	Kv value	Article
				mm					m³/h	
1.0460	DN15	PN40	EN 12982, Serie 1	130	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	3.3	12401954
1.0460	DN20	PN40	EN 12982, Serie 1	150	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	5.8	12711829
1.0460	DN25	PN40	EN 12982, Serie 1	160	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	9.2	12403928
1.0460	DN32	PN40	EN 12982, Serie 1	180	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	15	12439370
1.0460	DN40	PN40	EN 12982, Serie 1	200	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	23.3	12711830
1.0460	DN50	PN40	EN 12982, Serie 1	230	Hand wheel, rising with rising stem	Fixed disc	Bolted bonnet	Stainless steel	36	12711831

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.