


ECON® Gate valve Type: 290A Bronze Internal thread (BSPP) PN16



Characteristics

Type: 290A

Norm: EN (DIN)

Housing material: Bronze

Connection: Internal thread (BSPP)

Stem seal type: Gland seal

Primary spindle seal material: EPDM

Material bonnet: Brass

Bonnet gasket material: Fiber Gasket

Actuator material: Steel

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 120 °C

Maximum pressure difference at 20 °C: 16 bar

Application

- Recommended in: Utilities

DN	H	L	M	Weight
["]	mm	mm	mm	[kg]
3/8	68	39	50	0,3
1/2	74	38	55	0,3
3/4	79	44	55	0,4
1	91	47	60	0,6
1 1/4	112	53	70	0,9
1 1/2	126	58	80	1,2
2	143	64	90	1,9
2 1/2	178	76	110	2,8
3	206	82	120	4,3

Water, oil, air	Steam
12 bar- 120°C	8 bar - 120°C

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length mm	Operation	Type of bonnet	Sealing	Wedge material	Spindle material	Article
CC491K [RG5]	3/8" [10]	PN16	Manufacturer standard	39	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815473
CC491K [RG5]	1/2" [15]	PN16	Manufacturer standard	38	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815471
CC491K [RG5]	3/4" [20]	PN16	Manufacturer standard	44	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815472
CC491K [RG5]	1" [25]	PN16	Manufacturer standard	47	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815469

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length mm	Operation	Type of bonnet	Sealing	Wedge material	Spindle material	Article
CC491K [RG5]	1.1/4" [32]	PN16	Manufacturer standard	53	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815477
CC491K [RG5]	1.1/2" [40]	PN16	Manufacturer standard	58	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815475
CC491K [RG5]	2" [50]	PN16	Manufacturer standard	64	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815470
CC491K [RG5]	2.1/2" [65]	PN16	Manufacturer standard	76	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815474
CC491K [RG5]	3" [80]	PN16	Manufacturer standard	82	Hand wheel, non-rising with non-rising stem	Screwed	Brass	CW614N	CW614N	11815476

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.