



LEGRIS Series 1821 Stainless steel 316L straight adaptor male BSPT thread

Characteristics

Series: 1821

Ambient temperature: -20 / 180 °C

Maximum operating pressure [Bar]: 150 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
1821 21 21	Stainless steel 316L	External thread BSPT (R)	1/2	External thread BSPT (R)	1/2	23216294
1821 21 17	Stainless steel 316L	External thread BSPT (R)	1/2	External thread BSPT (R)	3/8	23216293
1821 13 13	Stainless steel 316L	External thread BSPT (R)	1/4	External thread BSPT (R)	1/4	23216288
1821 13 10	Stainless steel 316L	External thread BSPT (R)	1/4	External thread BSPT (R)	1/8	23216287
1821 10 10	Stainless steel 316L	External thread BSPT (R)	1/8	External thread BSPT (R)	1/8	23216285
1821 34 34	Stainless steel 316L	External thread BSPT (R)	1	External thread BSPT (R)	1	12261403
1821 34 27	Stainless steel 316L	External thread BSPT (R)	1	External thread BSPT (R)	3/4	12261402
1821 27 21	Stainless steel 316L	External thread BSPT (R)	3/4	External thread BSPT (R)	1/2	23216296
1821 27 27	Stainless steel 316L	External thread BSPT (R)	3/4	External thread BSPT (R)	3/4	23216297
1821 17 13	Stainless steel 316L	External thread BSPT (R)	3/8	External thread BSPT (R)	1/4	23216290

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.