



## LEGRIS Series 1821 Stainless steel 316L straight adaptor male NPT thread

### Characteristics

**Series:** 1821

**Ambient temperature:** -20 / 180 °C

**Maximum operating pressure [Bar]:** 150 bar

| Manufacturer ID | Material             | Threaded connection 1 | Connection 1 thread size | Threaded connection 2 | Connection 2 thread size | Article  |
|-----------------|----------------------|-----------------------|--------------------------|-----------------------|--------------------------|----------|
| 1821 22 22      | Stainless steel 316L | External thread (NPT) | 1/2                      | External thread (NPT) | 1/2                      | 23216295 |
| 1821 14 14      | Stainless steel 316L | External thread (NPT) | 1/4                      | External thread (NPT) | 1/4                      | 23216289 |
| 1821 11 11      | Stainless steel 316L | External thread (NPT) | 1/8                      | External thread (NPT) | 1/8                      | 23216286 |
| 1821 28 28      | Stainless steel 316L | External thread (NPT) | 3/4                      | External thread (NPT) | 3/4                      | 23216298 |
| 1821 18 18      | Stainless steel 316L | External thread (NPT) | 3/8                      | External thread (NPT) | 3/8                      | 23216292 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.