

LEGRIS 3313 series aluminium double manifold female BSPP thread



Characteristics

Series: 3313

Material: Aluminium

Maximum operating pressure [Bar]: 20 bar

Operating temperature: -10 to +80 °C

Port thread type	Port thread size in	Supply thread type	Supply thread size in	Number of outlets	Article
Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	1/8	2x3	23215063
Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	1/8	2x4	23215064
Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	1/8	2x2	23215062
Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	1/8	2x5	23215065
Internal thread BSPP [G]	3/8	Internal thread BSPP [G]	1/4	2x4	23215068
Internal thread BSPP [G]	3/8	Internal thread BSPP [G]	1/4	2x3	23215067
Internal thread BSPP [G]	3/8	Internal thread BSPP [G]	1/4	2x5	23215069
Internal thread BSPP [G]	3/8	Internal thread BSPP [G]	1/4	2x2	23215066
Internal thread BSPP [G]	1/2	Internal thread BSPP [G]	1/4	2x5	23215072

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.