

AKO Pinch valve Series: VMP Type: 209 Pneumatic operated Internal thread (BSPP)



Characteristics

Series: VMP

Type: 209

Norm: EN (DIN)

Housing material: POM

Connection: Internal thread (BSPP)

Standard thread connection: ISO 228-1


Operation: Pneumatic operated

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 80 °C

Application

- Recommended in: Food & Beverages, Machine Construction



Nominal inner diameter	Pressure rating	Material code hose/sleeve	Hose/sleeve material	Maximum control pressure bar	Maximum pressure difference at 20 °C bar	Article
3/8" [10]	PN6	EPDM	EPDM	8	6	12134355
3/8" [10]	PN6	NR-LX	NR (natural rubber) white	8	6	11924735
3/8" [10]	PN6	NR-X	NR (natural rubber)	8	6	11481590
1/2" [15]	PN6	NBR-LW	NR (natural rubber) white	8	6	11664526
1/2" [15]	PN6	NBR-LW	NR (natural rubber) white	8	6	11547023
1/2" [15]	PN6	NR-X	NR (natural rubber)	8	6	11481592
3/4" [20]	PN6	EPDM	EPDM	8	6	12362540
3/4" [20]	PN6	NBR	NBR	8	6	12218026
3/4" [20]	PN6	NR-X	NR (natural rubber)	8	6	11481851
1" [25]	PN6	EPDM	EPDM	8	6	12136649
1" [25]	PN6	EPDM-LS	EPDM	8	6	12378119
1" [25]	PN6	NBR	NBR	8	6	12042443
1" [25]	PN6	NR-LX	NR (natural rubber) white	8	6	11903687
1" [25]	PN6	NR-X	NR (natural rubber)	8	6	11480607
1.1/4" [32]	PN4	EPDM	EPDM	6.5	4.5	11738323
1.1/4" [32]	PN4	NBR	NBR	6.5	4.5	11662240
1.1/4" [32]	PN4	NR-LX	NR (natural rubber) white	6.5	4.5	12120958
1.1/4" [32]	PN4	NR-X	NR (natural rubber)	6.5	4.5	11884349
1.1/2" [40]	PN4	EPDM-LS	EPDM	6.5	4.5	12377876
1.1/2" [40]	PN4	NBR-LW	NR (natural rubber) white	6.5	4.5	11664525
1.1/2" [40]	PN4	NR-LX	NR (natural rubber) white	6.5	4.5	12160901
1.1/2" [40]	PN4	NR-X	NR (natural rubber)	6.5	4.5	11427223
2" [50]	PN4	EPDM	EPDM	6.5	4.5	12148343
2" [50]	PN4	EPDM-LS	EPDM	6.5	4.5	11453166
2" [50]	PN4	NBR	NBR	6.5	4.5	11520369
2" [50]	PN4	NR-LX	NR (natural rubber) white	6.5	4.5	11531649
2" [50]	PN4	NR-X	NR (natural rubber)	6	4	11425722

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.