



Compensator in PTFE type RX 80/3 with flanges

Characteristics

Type: 80/3

Application

- Recommended in: Food & Beverages

Colour	Face to Face length mm	Type	Maximum operating pressure at 20 °C bar	Configuration with movement limiter	Bellows material	Nominal inner diameter	Pressure rating flange	Flange material	Article
White	50	80/3	10	No	Polytetrafluoroethylene (PTFE)	DN32	PN16	Carbon steel	10040061
White	50	80/3	10	No	Polytetrafluoroethylene (PTFE)	DN40	PN16	Carbon steel	10040062
White	75	80/3	10	No	Polytetrafluoroethylene (PTFE)	DN50	PN16	Carbon steel	10040063
White	75	80/3	10	No	Polytetrafluoroethylene (PTFE)	DN65	PN10	Carbon steel	10040064
White	100	80/3	10	No	Polytetrafluoroethylene (PTFE)	DN80	PN16	Carbon steel	10040065
White	100	80/3	85	No	Polytetrafluoroethylene (PTFE)	DN100	PN16	Carbon steel	10040066
White	125	80/3	7	No	Polytetrafluoroethylene (PTFE)	DN250	PN16	Carbon steel	10040070
White	125	80/3	85	No	Polytetrafluoroethylene (PTFE)	DN125	PN16	Carbon steel	10040067
White	150	80/3	3	No	Polytetrafluoroethylene (PTFE)	DN500	PN16	Carbon steel	10040071
White	150	80/3	7	No	Polytetrafluoroethylene (PTFE)	DN200	PN10	Carbon steel	10040069
White	150	80/3	85	No	Polytetrafluoroethylene (PTFE)	DN150	PN16	Carbon steel	10040068

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.