




WILLBRANDT Compensator type 50 colour red - suitable for potable water - flanges - steel or stainless steel - model 'A'



Characteristics

Type: 50



Colour code	Face to Face length	Type	Maximum operating pressure at 20 °C	Vacuum-resistance at 20 °C	Configuration with movement limiter	Bellows inside wall material	Nominal inner diameter	Article
	mm		bar	%				
Red/DW	130	50	16	20	No	IIR (Butyl)	DN20	11256507
Red/DW	130	50	16	20	No	IIR (Butyl)	DN25	11256508
Red/DW	130	50	16	20	No	IIR (Butyl)	DN32	11256509
Red/DW	130	50	16	20	No	IIR (Butyl)	DN40	11256510
Red/DW	130	50	16	20	No	IIR (Butyl)	DN50	11256511
Red/DW	130	50	16	20	No	IIR (Butyl)	DN65	11256512
Red/DW	130	50	16	20	No	IIR (Butyl)	DN80	11256513
Red/DW	130	50	16	20	No	IIR (Butyl)	DN100	11256514
Red/DW	130	50	16	20	No	IIR (Butyl)	DN125	11256515
Red/DW	130	50	16	20	No	IIR (Butyl)	DN150	11256516
Red/DW	130	50	16	20	No	IIR (Butyl)	DN200	11256517
Red/DW	130	50	16	20	No	IIR (Butyl)	DN250	11256518
Red/DW	130	50	16	20	No	IIR (Butyl)	DN300	11256519
Red/DW	200	50	16	20	No	IIR (Butyl)	DN350	11070458
Red/DW	200	50	16	20	No	IIR (Butyl)	DN400	10040324
Red/DW	200	50	16	20	No	IIR (Butyl)	DN500	10040325
Red/DW	200	50	16	20	No	IIR (Butyl)	DN600	10040326
Red/DW	250	50	10	20	No	IIR (Butyl)	DN700	11050128
Red/DW	250	50	10	20	No	IIR (Butyl)	DN800	10040327
Red/DW	300	50	10	20	No	IIR (Butyl)	DN900	11256520
Red/DW	300	50	10	20	No	IIR (Butyl)	DN1000	11256521

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.