



Flow meter series M23

Characteristics

Series: M23
Type: 8185
Mounting: Vertical
Internal spring: No
Process connection: Glued sleeve
Calibration: Water
Accuracy: 4.0 %
Accuracy standard: VDI/VDE 3513
Material of connection: PVC
Sealing: FPM

Characteristics (2)

Material float catcher: PVDF
With needle valve: No
Explosion-proof: No
Medium temperature: 0 / 60 °C
Ambient temperature: 0 / 55 °C

Size process connection	Measuring range	Measuring unit	Material measuring tube	Float material	Max. pressure bar	Article
32 mm	50 / 500	l/h	Trogramid	PVDF	10	10059219
32 mm	50 / 500	l/h	Polysulfon	PVDF	10	10070885
32 mm	100 / 1000	l/h	Trogramid	PVDF	10	10059220
32 mm	100 / 1000	l/h	Polysulfon	PVDF	10	10070886
50 mm	200 / 2000	l/h	Trogramid	PVDF	10	10059221
50 mm	200 / 2000	l/h	Polysulfon	PVDF	10	10070887
50 mm	300 / 3000	l/h	Trogramid	PVDF	10	10059222
50 mm	300 / 3000	l/h	Polysulfon	PVDF	10	10070888
50 mm	600 / 6000	l/h	Trogramid	PVDF	10	11603056
50 mm	600 / 6000	l/h	Polysulfon	PVDF	10	11935813
63 mm	1500 / 15000	l/h	Trogramid	PVDF	10	11935654
63 mm	1500 / 15000	l/h	Polysulfon	PVDF	10	10070890
75 mm	2000 / 20000	l/h	Trogramid	PVDF	10	10059225
75 mm	2000 / 20000	l/h	Polysulfon	PVDF	10	10070891
75 mm	3000 / 30000	l/h	Trogramid	PVDF	10	10059226
75 mm	3000 / 30000	l/h	Polysulfon	PVDF	10	10070892
75 mm	8000 / 60000	l/h	Trogramid	PVC	10	10059227
75 mm	8000 / 60000	l/h	Polysulfon	PVC	10	10070883

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.