



KROHNE Flow meter series DK46

Characteristics

Series: DK46
Type: 8193
Mounting: Vertical
Internal spring: No
Process connection: Internal thread [NPT]
Calibration: Water
Accuracy: 4.0 %
Accuracy standard: VDI/VDE 3513
Material of connection: Brass, Nickel-plated
Housing material: PC
Sealing: FPM

Characteristics [2]

Material float catcher: Brass, Nickel-plated
With needle valve: Yes
Explosion-proof: No
Medium temperature: -5 / 100 °C
Ambient temperature: -20 / 100 °C

Size process connection	Measuring range	Measuring unit	Material measuring tube	Float material	Max. pressure bar	Article
1/4" [8]	0.5 / 5	l/h	Glass	Stainless steel 316L	10	10070940
1/4" [8]	1.2 / 12	l/h	Glass	Stainless steel 316L	10	10070941
1/4" [8]	2.5 / 25	l/h	Glass	Stainless steel 316L	10	10070945
1/4" [8]	4 / 40	l/h	Glass	Stainless steel 316L	10	10070946
1/4" [8]	6 / 60	l/h	Glass	Stainless steel 316L	10	10070947
1/4" [8]	10 / 100	l/h	Glass	Stainless steel 316L	10	10070942
1/4" [8]	12 / 120	l/h	Glass	Stainless steel 316L	10	10070943
1/4" [8]	16 / 160	l/h	Glass	Stainless steel 316L	10	10070944
1/4" [8]	0.25 / 2.5	l/h	Glass	Stainless steel 316L	10	10070939

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.