



Flow meter fig. 8183 series M123 plastic glued sleeve

Characteristics

Series: M123
Type: 8183
Mounting: Vertical
Internal spring: No
Nominal inner diameter: DN25
Process connection: Glued sleeve
Calibration: Water
Accuracy: 4.0 %
Accuracy standard: VDI/VDE 3513

Characteristics [2]

Material of connection: PVC
Sealing: EPDM
Material float catcher: PVDF
With needle valve: No
Explosion-proof: No
Ambient temperature: 0 / 55 °C

Size process connection	Measuring range	Measuring unit	Material measuring tube	Float material	Max. pressure bar	Article
16 mm	1.5 / 15	l/h	Polysulfon	PVDF	10	12304411
16 mm	2.5 / 25	l/h	Polysulfon	PVDF	10	12336873
16 mm	5 / 50	l/h	Polysulfon	PVDF	10	11467263
16 mm	10 / 100	l/h	Polysulfon	PVDF	10	12099074
20 mm	15 / 150	l/h	Polysulfon	PVDF	10	11919441
20 mm	20 / 200	l/h	Polysulfon	PVDF	10	11478901
32 mm	15 / 150	l/h	Polysulfon	PVDF	10	12725655
32 mm	50 / 500	l/h	Polysulfon	PVDF	10	12099078
32 mm	100 / 1000	l/h	Polysulfon	PVDF	10	12725654
32 mm	30 / 300	l/h	Polysulfon	PVDF	10	11532393

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.