



GF Transition flange Series: 701 PP, glass filled Black Norm: ASME

Characteristics

Series: 701

Norm: ASME

Flange type: Push-on flange

Material: PP, glass filled

Colour: Black

Application

- Can be used in combination with collar bushing and flat seal

Technical Information

- Connection dimensions in accordance with ANSI/ASME B 16.5, class 150
- Flange bore class 150

Execution

- Mounting method in accordance with ANSI/ASME B 16.5, class 150 Only use undamaged and clean products
- 1 seal per connection
- Mount the collar bushings completely parallel
- Grease the nuts and bolts
- Observe and mark the prescribed tightening sequence
- Tighten to the specified torque in five steps: Hand-tight/wrench-tight, 30%, 60%, 100%, full check [clockwise]
- Tighten the connections after pressing out

Pressure rating flange	Nominal inner diameter	External tube diameter of connection	Inner diameter of push-on flange	Pitch circle	Number of bolt holes	Diameter bolt hole	Thickness flange	Article
		mm	mm	mm		mm	mm	
PN16	1/2"		28	60	4	16	16	11267636
PN16	1.1/4"		51	350	12	22	38	11267639
PN16	DN65	75	92	140	4	19	26	11259693
PN16	DN250	250	310	362	12	26	38	11385914
PN16	DN300	300	348	432	12	26	42	11385924

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.