



GF Transition flange Series: 700 PP with steel core Black

Norm: EN 1092-1/02 DIN 2501

Characteristics

Series: 700
Norm: EN 1092-1/02
Flange type: Push-on flange
Flange standard: DIN 2501
Material: PP with steel core
Colour: Black

Application

- Can be used in combination with a welding neck collar and a flat seal
- Suitable for butt weld fittings

Technical Information

- Connection dimensions in accordance with EN 1092/DIN 2501
- Flange bore PN10

Execution

- Mounting method in accordance with DVS 2210-1, addendum 3, and DIN 16962-12 Only use undamaged and clean products
- 1 seal per connection
- Mount the collar bushings completely parallel
- Grease the nuts and bolts
- Observe and mark the prescribed tightening sequence
- Tighten to the specified torque in five steps: Hand-tight/wrench-tight, 30%, 60%, 100%, full check [clockwise]
- Tighten the connections after pressing out

Pressure rating flange	Nominal inner diameter	External tube diameter of connection	Inner diameter of push-on flange	Pitch circle	Number of bolt holes	Diameter bolt hole	Thickness flange	Article
		mm	mm	mm		mm	mm	
PN16	DN15	20	28	65	4	14	12	11176663
PN16	DN32	40	51	100	4	18	16	11176666
PN16	DN50	63	78	125	4	18	20	11176668
PN16	DN65	75	92	145	4	18	20	11176669
PN16	DN80	90	108	160	8	18	20	11176670
PN16	DN100	110	128	180	8	18	20	12250992

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.