



GF Transition flange Series: 702 PVC-U Norm: ASME

Characteristics

Series: 702
Norm: ASME
Flange type: Push-on flange
Material: PVC-U
Colour: Black

Application

- Can be used in combination with collar bushing and flat seal

Technical Information

- Connection dimensions in accordance with ANSI/ASME B 16.5, class 150
- Flange bore class 150

Execution

- Mounting method in accordance with ANSI/ASME B 16.5, class 150 Only use undamaged and clean products
- 1 seal per connection
- Mount the collar bushings completely parallel
- Grease the nuts and bolts
- Observe and mark the prescribed tightening sequence
- Tighten to the specified torque in five steps: Hand-tight/wrench-tight, 30%, 60%, 100%, full check [clockwise]
- Tighten the connections after pressing out

Pressure rating flange	Nominal inner diameter	Inner diameter of push-on flange	Pitch circle	Number of bolt holes	Diameter bolt hole	Thickness flange	Article
		mm	mm		mm	mm	
PN10	1/2"	28	60	4	16	11	11199525
PN10	1"	42	79	4	16	14	11171515
PN10	2.1/2"						11399043
PN10	3"	110	152	4	19	20	11097739
PN10	4"			4			11413755

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.