



CHEMVALVE-SCHMID Wafer type check valve Series: ChemDisc DTEF Type: 72628 Stainless steel, TFM lined Wafer type PN10

TFM wafer type check valve with stainless steel casing, disc and spring, pressure class PN10.

This is a dual-use or controlled item. When exporting this item outside the EU an export license is required from the regulatory authorities.

Characteristics

Series: ChemDisc DTEF

Type: 72628

Norm: EN [DIN]

Housing material: Stainless steel, TFM lined

Material quality: 1.4301 with TFM conductive lining (black)

Connection: Wafer type

Face to Face norm: EN 558, Series 52

With spring: Yes

Maximum medium temperature (continuous): 160 °C

Maximum pressure difference at 20 °C: 10 bar

Application

- General industry.
- Chemical industry.
- Food industry.
- Corrosive liquids and gases.
- Suitable for horizontal and vertical (rising flow) mounting.
- Recommended in: Chemical

Technical Information


- Mounting between EN [DIN] flanges.
- Face to Face length: EN 558, Series 52.
- Testing: EN 12266-1.
- Leakage Class EN 12266-1: with PTFE or TFM seal Class D, with EPDM, NBR or FKM seal Class A.
- TFM material is black, conductive (Atex) and suitable for foodstuffs (FDA, EC1935/2004).
- Information on opening pressures on request.

Options

- Available with soft seal: EPDM, NBR, FKM or PTFE.
- Available in larger sizes.
- Available with Class 150 flanges.
- Calculation of the correct size based on process flow data.

Size table:

DN	d mm	D mm	L mm	Weight kg
DN20	20	61	31.5	0.1
DN25	25	71	35.5	0.3
DN32	32	82	40	0.4
DN40	40	92	45	0.55
DN50	50	107	56	0.8
DN65	65	127	63	1.3
DN80	80	142	71	2.5



Nominal inner diameter	Standard connection	Pressure rating	Face to Face length mm	Valve shape	Kv value m³/h	Sealing	Material disc	Spring material	Minimum medium temperature (continuous) °C	Article
DN20	EN (DIN)	PN10	31.5	Disc	5.7	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	14046559
DN25	EN (DIN)	PN10	35.5	Disc	11.1	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	13494020
DN32	EN (DIN)	PN10	40	Disc	21.2	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	14046560
DN40	EN (DIN)	PN10	45	Disc	21.6	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	14046561
DN50	EN (DIN)	PN10	56	Disc	41.73	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	14046562
DN65	EN (DIN)	PN10	63	Disc	70.5	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	14046563
DN80	EN (DIN)	PN10	71	Disc	91.33	TFM	TFM conductive (black)	Hastelloy C4, PFA sheathed	-10	14046564

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.