



## LINK-SEAL Link seal Series: OS NBR Stainless steel 316 (V4A)

**Link-Seal wall pass - Corrosion resistant (performance electrical insulation). Temperature resistance: -40 ° C to +70° C.**

Link: NBR rubber, resistant to oil, grease, aromatic hydrocarbons, solvents and oil-based media. Bolts and nuts grade AISI316.

Pressure plate: PA 6.6 reinforced with 30% glass fiber for electrical insulation and cathodic protection. Rubber color: green.

### Features:

- Quick and easy assembly
- Safe and long life
- Resistant to heat, it can even be fireproof

### Advantages:

- Saves time when by installation
- Absorbs noise and shock
- Close perfectly, even with off-center wall penetrations
- Easily removable

### Fields of application:

- Pipi-lines
- Industry
- Chemistry
- Storage companies
- Hospitals
- Water Treatment
- Pools

### Characteristics

**Series:** OS

**Material:** NBR

**Airtight:** Yes

**Watertight:** Yes

**Stench-tight:** Yes

**Sound-absorbing:** Yes

**Material bolts and nuts:** Stainless steel 316 (V4A)

**Minimum medium temperature (continuous):** -40 °C

**Maximum medium temperature (continuous):** 100 °C

| Type wall seal | Wall/partition/floor thickness<br>mm | Colour | Article  |
|----------------|--------------------------------------|--------|----------|
| LS 200-OS-316  | 75                                   | Green  | 11185523 |
| LS 275-OS-316  | 75                                   | Green  | 11537871 |
| LS 300 OS-316  | 100                                  | Green  | 11042375 |
| LS 325-OS-316  | 120                                  | Green  | 11295159 |
| LS 360-OS-316  | 120                                  | Green  | 12304381 |
| LS 400 OS-316  | 140                                  | Green  | 11051985 |
| LS 410 OS-316  | 140                                  | Green  | 11665996 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

| Type wall seal | Wall/partition/floor thickness<br>mm | Colour | Article  |
|----------------|--------------------------------------|--------|----------|
| LS 425 OS-316  | 140                                  | Green  | 11119980 |
| LS 500-OS-316  | 150                                  | Green  | 11554436 |
| LS 525-OS-316  | 150                                  | Green  | 11652138 |
| LS 575-OS-316  | 150                                  | Green  | 12554324 |
| LS 615-OS-316  | 150                                  | Green  | 12554325 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.