

U-cup type 0022




Characteristics

Type: 0022

Max. operating pressure: 400 bar

Maximum speed: 0.5 m/s



Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Temperature range	Article
mm	mm	mm	mm		°C	
22	32	9	8	PUR	-35 / 100	10018092
25	35	9	8	PUR	-35 / 100	10018093
30	45	11	10	PUR	-35 / 100	10018137
32	40	7	6	PUR	-35 / 100	11273673
35	45	11	10	PUR	-35 / 100	10068539
35	50	11	10	PUR	-35 / 100	10018139
37	47	9	8	PUR	-35 / 100	11330077
40	50	11	10	PUR	-35 / 100	10018141
40	55	11	10	PUR	-35 / 100	10018142
45	53	8	7	PUR	-35 / 100	11330017
50	60	8	7	PUR	-35 / 100	10018095
50	65	11	10	PUR	-35 / 100	10018145
60	70	13	12	PUR	-35 / 100	10018147
60	75	13	12	PUR	-35 / 100	10018149
65	75	13	12	PUR	-35 / 100	10018150
65	80	13	12	PUR	-35 / 100	10018151
65	85	13	12	PUR	-35 / 100	10018152
70	80	13	12	PUR	-35 / 100	10018153
70	90	13	12	PUR	-35 / 100	10018154
75	90	11	10	PUR	-35 / 100	10018156
80	95	13	12	PUR	-35 / 100	10068540
80	100	13	12	PUR	-35 / 100	10018266
100	115	13	12	PUR	-35 / 100	10018442

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Temperature range	Article
mm	mm	mm	mm		°C	
100	120	13	12	PUR	-35 / 100	10018443
110	130	16	15	PUR	-35 / 100	10018448
125	145	16	15	PUR	-35 / 100	10018449
				PUR		10018138
				PUR		10018503
				PUR		10018440

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.