



FREUDENBERG Compact seal type S8

Characteristics

Type: S8

Max. operating pressure: 250 bar

Maximum speed: 0.5 m/s



Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Compound	Temperature range	Article
mm	mm	mm	mm			°C	
5	12	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018638
6	13	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018639
8	15	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018640
10	17	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018681
12	19	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018682
15	23	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018683
16	24	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018684
18	26	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018685
20	28	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018686
22	30	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018687
25	33	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018688
28	36	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018689
30	38	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018690
32	40	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018691
35	43	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018692
36	44	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018693
40	48	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018694
42	50	6.4	6	NBR/fabric	70 NBR B209	-30 / 100	10018695
45	55	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018575
50	58	8.5	8	NBR/fabric	70 NBR B209	-30 / 100	10018747
50	60	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018576
50	62	9.5	9	NBR/fabric	70 NBR B209	-30 / 100	10018748

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Compound	Temperature range	Article
mm	mm	mm	mm			°C	
55	65	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018577
56	66	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018578
60	70	8	7.5	NBR/fabric	70 NBR B209	-30 / 100	10018579
65	77	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018697
70	82	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018698
75	87	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018699
80	92	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018700
85	97	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018701
90	102	9.6	9	NBR/fabric	70 NBR B209	-30 / 100	10018785
100	115	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018786
110	125	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018787
115	130	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018788
120	135	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018750
125	140	12	11.3	NBR/fabric	70 NBR B209	-30 / 100	10018789
130	145	11	10.2	NBR/fabric	70 NBR B209	-30 / 100	10018790
140	160	16	15	NBR/fabric	70 NBR B209	-30 / 100	11131828
150	170	16	15	NBR/fabric	70 NBR B209	-30 / 100	10018792
160	180	16	15	NBR/fabric	70 NBR B209	-30 / 100	10018793
165	185	16	15	NBR/fabric	70 NBR B209	-30 / 100	11013585
180	200	16	15	NBR/fabric	70 NBR B209	-30 / 100	10018794
200	220	16	15	NBR/fabric	70 NBR B209	-30 / 100	11295888
							10018696
NBR/fabric							10018796

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.