

FREUDENBERG Rotomatic type M17

Characteristics



Type: M17

Application: Rod seal

Material seal: NBR/fabric

Max. operating pressure: 200 bar

Maximum speed: 0.1 m/s



Internal diameter mm	Outer diameter mm	Groove width mm	Seal height mm	Compound	Temperature range °C	Article
						10018604
						10018519
12	20	6.5	6	80 NBR B246	-30 / 80	10018651
20	28	6.5	6	80 NBR B246	-30 / 80	10018653
30	40	8	7.5	80 NBR B246	-30 / 80	10018515
40	52	8	7.5	80 NBR B246	-30 / 80	10018516
45	57	8	7.5	80 NBR B246	-30 / 80	10018517
50	62	8	7.5	80 NBR B246	-30 / 80	10018518
55	67	8	7.5	80 NBR B246	-30 / 80	10018654
60	75	11	10	80 NBR B246	-30 / 80	10018602
70	85	11	10	80 NBR B246	-30 / 80	10018603
80	95	11	10	80 NBR B246	-30 / 80	10018605
90	110	13	12	80 NBR B246	-30 / 80	10018655
100	115	11	10	80 NBR B246	-30 / 80	11082574
100	120	13	12	80 NBR B246	-30 / 80	10018724
110	130	13	12	80 NBR B246	-30 / 80	10018725
115	135	13	12	80 NBR B246	-30 / 80	10018726
200	225	16	15	80 NBR B246	-30 / 80	10018727

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.