

Compact seal type ERKO


Characteristics

Type: ERKO

Principle of operation: Double acting

Max. operating pressure: 400 bar

Maximum speed: 0.5 m/s



Bore diameter	Groove diameter	Groove width	Material seal	Material guide ring	Temperature range	Article
mm	mm	mm			°C	
40	32	15.5	NBR/fabric	POM	-30 / 100	10019203
45	37	15.5	NBR/fabric	POM	-30 / 100	10019204
50	38	20.5	NBR/fabric	POM	-30 / 100	10019205
60	48	20.5	NBR/fabric	POM	-30 / 100	10019206
63	51	20.5	NBR/fabric	POM	-30 / 100	10019207
70	58	20.5	NBR/fabric	POM	-30 / 100	10019208
90	76	22.5	NBR/fabric	POM	-30 / 100	10019210
100	86	22.5	NBR/fabric	POM	-30 / 100	10019211
110	96	22.5	NBR/fabric	POM	-30 / 100	10019212
120	106	22.5	NBR/fabric	POM	-30 / 100	10019237
150	133	26.5	NBR/fabric	POM	-30 / 100	10068542
200	180	31.5	NBR/fabric	POM	-30 / 100	10019239
220	200	31.5	NBR/fabric	POM	-30 / 100	10019240

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.