

FREUDENBERG U-cup type N100


Characteristics

Type: N100

Material seal: NBR

Max. operating pressure: 100 bar

Maximum speed: 0.5 m/s



Internal diameter	Outer diameter	Groove width	Seal height	Compound	Temperature range	Article
mm	mm	mm	mm		°C	
8	16	9	8	90 NBR 109	-30 / 100	11292772
12	24	11	10	90 NBR 109	-30 / 100	11292770
18	30	11	10	90 NBR 109	-30 / 100	11292768
20	35	11	10	90 NBR 109	-30 / 100	11292767
22	34	11	10	90 NBR 109	-30 / 100	11292766
22	38	11	10	90 NBR 109	-30 / 100	11292765
30	42	11	10	90 NBR 109	-30 / 100	11292763
30	45	11	10	90 NBR 109	-30 / 100	11292762
30	50	13	12	90 NBR 109	-30 / 100	11326934
35	50	11	10	90 NBR 109	-30 / 100	11292761
45	60	11	10	90 NBR 109	-30 / 100	11333504
55	75	13	12	90 NBR 109	-30 / 100	11292756
75	95	13	12	90 NBR 109	-30 / 100	11333497
80	100	13	12	90 NBR 109	-30 / 100	11292753
120	145	19	18	90 NBR 109	-30 / 100	11292749
120	150	19	18	90 NBR 109	-30 / 100	11292748
130	160	19	18	90 NBR 109	-30 / 100	11203475
160	180	16	15	90 NBR 109	-30 / 100	11316314
170	200	23	22	90 NBR 109	-30 / 100	11292746

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.