

Wiper type 008P PUR




Characteristics

Type: 008P

Groove type: Closed

Principle of operation: Single acting

Maximum speed: 1 m/s



Operating conditions			
Media	Mineral Oils [DIN 51524]	HFA and HFB	HFC
Temperature	-30°C + 100°C	+5°C + 50°C	-30°C + 60 °C
Speed	≤1,0 m/s	≤1,0 m/s	≤1,0 m/s

Note: The above data are maximum values, they may only be maintained for short periods of time and cannot be used at the same time simultaneously.

Surface roughness		
	Ra	Rmax
Sliding Surface	≤0,4 µm	≤3,2 µm
Groove Base	≤1,6 µm	≤10 µm
Groove Flanks	≤3,2 µm	≤16 µm

Hardware tolerances					
Dimension	Ød	ØD	ØD1	L	L1
Tolerance	f8	H10	H10	+0,2/-0 mm	+0,2/-0 mm

Rod diameter	Groove diameter	Groove width	Seal height	Material seal	Temperature range	Article
mm	mm	mm	mm		°C	
28	36	4	7	PUR	-30 / 100	14399856
38	46	4	7	PUR	-30 / 100	10018001

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.